

***Inclusion of Tropical Storms for
the Combined Total Storm Tide Frequency Restudy
for Martin County, Florida***

S. Y. Wang

**Engineering, Hydrology & Geology Program
Division of Water Resource Management
Florida Department of Environmental Protection
January 2014**

2600 Blair Stone Road, M.S. 3500
Tallahassee, Florida 32399
www.dep.state.fl.us/water



Table of Contents

1.0	Background	1
2.1	Introduction and Data Source	1
2.2	Storm Frequency and Direction	1
2.3	Radius to Maximum Winds and Central Pressure Deficit	2
2.4	Forward Speed	5
2.5	Track Position	5
3.1	Simulation of a n-Year Sequence of Storm Associated Storm Tides	7
3.2	Simulation	9
3.3	Computation of Return Periods	10
4.0	Results	11
	REFERENCES	13
	APPENDIX A	14
	APPENDIX B	17

List of Figures

<u>Figure</u>		<u>Page</u>
1	Cumulative Probability Distribution of Storm Track Direction, θ_N	2
2	Cumulative Probability Distribution of Radius to Maximum Winds, R, for Landfalling and Exiting Storms	3
3	Cumulative Probability Distribution of Radius to Maximum Winds, R, for Alongshore Storms	3
4	Cumulative Probability Distribution of Central Pressure Deficit, Δp for Landfalling and Alongshore Storms	4
5	Cumulative Probability Distribution of Central Pressure Deficit, Δp for Exiting Storms	4
6	Cumulative Probability Distribution of Storm Translation Speed, V_F	5
7	Cumulative Probability Distribution of Landfalling Distance, Y_F , for Landfalling And Exiting Storms	6
8	Cumulative Probability Distribution of Offshore Distance, X_L , for Alongshore Storms	6
9	Flow Chart for Two-Dimensional Storm Tide Simulations	8
10	Combined Total Storm Tide Elevation Versus Return Period for Study Area	11

List of Tables

<u>Table</u>		<u>Page</u>
I	Combined Total Storm Tide Values for Various Return Periods	12

1.0 Background

In accordance with the objectives and rationale of the Florida Coastal Construction Control Line, the establishment of the line is based on the damage potential of 100 year return period hurricanes. A report entitled “Combined Total Storm Tide Frequency for Martin County, Florida” (Reference (1)) was submitted to FDEP in July, 1984. This study includes the most updated tropical storms and hurricanes in the storm surge simulations. Since the methodology and procedures used for this study are the same as for the report mentioned above, only the storm statistics and the results are presented in this report.

2.1 Introduction and Data Source

The statistical parameters are based on historical storm data as presented in References (2) and (3). In brief, the empirical cumulative probability distributions are plotted for each of the parameters of interest and are then approximated by a series of straight line segments for computer application. All of the parameters are considered to be independent. The following subsections describe the statistical characteristics of the individual parameters of interest.

2.2 Storm Frequency and Direction

The storms causing appreciable storm tides in the vicinity of the Martin County shoreline are classified as "landfalling", "exiting" or "alongshore" storms. Reasonably good data are available describing the characteristics of the storms impacting the area from 1900 to 2012. For purposes of this report, the data contained in References (2) and (3) that fall within a 250 n. mi. segment of the coast comprising the study area are used. The storm direction is defined here as the azimuth from which the storm is translating at the time of landfall, or, if an alongshore storm, when in close proximity to the site.

For purposes of this study, landfalling and exiting storms are considered to be of possible significance if they made landfall within a 250 n. mi. segment of the coast comprising the study area. This segment is extended 125 n. mi. north and 125 n. mi. south from the midpoint of the Martin County shoreline. Accordingly, there were 25 landfalling, 46 exiting and 7 alongshore storms occurring in the years 1900 through 2012. The table in Appendix A lists the storms used in this study.

Based on historical data, it is expected that within a 1,000 year period a total of 690 storms will occur within the 250 n. mi. segment of the coast comprising the study area. Of the 690 storms, 221 will be landfalling, 407 exiting and 62 alongshore storms.

For purposes of computer use, the cumulative probability distribution of storm track direction (θ_N) is presented in Figure 1.




Figure 1: Cumulative Probability Distribution of Storm Track Direction, θ_N

2.3 Radius to Maximum Winds and Central Pressure Deficit

The cumulative probability distribution of radius to maximum winds for landfalling and exiting storms is presented in Figures 2. Figure 3 presents the same for alongshore storms. The cumulative probability distributions of pressure deficit for landfalling and alongshore storms is presented in Figure 4. Figure 5 presents the same for exiting storms.




Figure 2: Cumulative Probability Distribution of Radius to the Maximum Wind, R, for Landfalling and Exiting Storms




Figure 3: Cumulative Probability Distribution of Radius to the Maximum Wind, R, for Alongshore Storms




Figure 4: Cumulative Probability Distribution of Central Pressure Deficit, Δp for Landfalling and Alongshore storms




Figure 5: Cumulative Probability Distribution of Central Pressure Deficit, Δp for Exiting storms

2.4 Forward Speed

The cumulative probability distribution of the forward speed of translation for landfalling, exiting and alongshore storms is presented in Figure 6.




Figure 6: Cumulative Probability Distribution of Translation Speed , V_F

2.5 Track Position

For the landfalling and exiting storms, the track position is determined by the y coordinate, Y_F , representing the landfalling or exiting point. Figure 7 presents the cumulative probability distribution for the actual landfalling and exiting position, Y_F , for landfalling and exiting storms. Figure 8 presents the cumulative probability distribution for the actual offshore distance, X_L , for alongshore storms.




Figure 7: Cumulative Probability Distribution of Landfalling Distance, Y_F , for Landfalling and Exiting Storms




Figure 8: Cumulative Probability Distribution of Offshore Distance, X_L , for Alongshore Storms

3.1 Simulation of a n-Year Sequence of Storm Associated Storm Tides

With the statistical characteristics of historical storms available and the two-dimensional model calibrated as described in the preceding section, the simulation shown in Figure 9 is carried out.

The first phase of the simulation comprises the selection of the storm characteristics in accordance with the historical data. In each storm, this involves the following:

- 1) Quantifying Δp , R , V_F , θ_N and storm track in accordance with the historical probabilities.
- 2) For these characteristics, a random astronomical tide from the storm season is generated as a boundary condition to the two-dimensional numerical model and the model is run to determine the storm surge at the site of interest. This storm surge with dynamic wave set up is then adjusted in accordance with the factors obtained from the two-dimensional model calibration runs for the landward grid at each time step to yield the combined total storm tide.
- 3) Determining whether enough storms have been simulated for the n-year simulation.
- 4) After the required number of storms and associated storm tides have been simulated, the peak water levels for each storm are ranked and the return period, TR , is calculated, according to

$$TR = 1000/M$$

where M is the rank of the combined total storm tide level. (For example, since the simulation was carried out for a 1,000 year period, the highest combined total tide level would have a return period of 1,000 years, the tenth highest water level would have a return period of 100 years, etc.). Finally, by presenting these results on semi-log paper, it is possible to interpolate return periods of 5, 10, 15, 20, 25, 30 and 50 years.




Figure 9: Flow Chart for Two-Dimensional Storm Tide Simulations

3.2 Simulation

To summarize information presented earlier, this phase includes the simulation of the occurrence of 1,000 years of storms along a shoreline segment of 250 n. mi. The simulated storms are given directional distributions according to Figure 5. In an average 1,000 year period, there would be a total of 690 storms.

Selection of Storm Parameters - Each of the five idealized storm parameters, [Radius to Maximum Winds, R ; Central Pressure, p_o (or Central Pressure Deficit, Δp); Track Direction, θ_N ; System Forward Speed, V_F ; and Track Position] is determined randomly in accordance with the associated cumulative probability distribution functions. The procedure is described below for the track direction, θ_N , and is similar for all other variables.

The approximate piece-wise linear cumulative probability distribution function for track direction, θ_N , is shown in Figure 5. The nature of this function is such that the predominant directions are those where the function rises steeply. To randomly select a track direction in accordance with the distribution function, the computer first generates a random number between 0 and 1 and then selects the θ_N corresponding to that cumulative probability. The other four parameters are determined similarly with a separate and independent random number being generated for each parameter and the appropriate cumulative probability distribution used.

Calculation of Storm Surge with the Effect of Astronomical Tide - A particular storm can be "phased" such that the maximum resulting storm surge is increased or decreased by astronomical tidal fluctuations. Considering the predicted ocean astronomical tidal fluctuations off Martin County from June 1 to November 30, 1984 to be representative of those occurring during the storm season and assuming the phasing of storm occurrence and astronomical tides to be independent, the combination of these tidal components is carried out in the following manner.

With the storm parameters established, a starting time for the storm is selected randomly between June 1 and November 30, 1984. The corresponding astronomical tide at the starting time is generated and varies with time thereafter according to the input astronomical tide data. The calculation of the storm surge history by the calibrated two-dimensional model is thus phased with the astronomical tide to yield the combined storm surge and astronomical tide water level history at the site of interest.

3.3 Computation of Return Periods

With a sufficient number (690) of maximum combined total storm tides simulated to represent a typical 1,000 year time interval, the tides associated with various return periods of interest are determined. The 690 maximum combined total storm tides are ranked in descending order with the largest occurring first. The return period, TR, of the ranked tides is then

$$TR = 1000 / M$$

in which

TR = Return period in years between expected exceedances of the associated maximum storm tide

M = Rank of maximum storm tide

As an example, for M = 690 (associated with the lowest water level) the return period would be:

$$TR_{690} = 1000 / 690 = 1.45 \text{ years}$$

which indicates that the smallest storm tide could be expected to be exceeded approximately once every 2 years. As a second example, the return period for M = 20 is

$$TR_{20} = 1000/20 = 50 \text{ years}$$

The ranked maximum combined total storm tides and associated return periods can be plotted and the combined total storm tide associated with any return period determined. Finally, it is noted that it is possible to run the simulation procedure any number of times to determine the stability (constancy) of any combined total storm tide associated with a given return period. It is expected that for a 1,000 year simulation, the storm tides associated with the longer (> 250 year) return periods would not be well-defined by one simulation and would exhibit variation from simulation to simulation. However, the storm tides associated with the lower return periods (TR < 100 years) should be well-defined by a 1,000 year simulation and hence are not expected to vary significantly for various simulations.

4.0 Results

Five 1,000-year simulations for Martin County were carried out employing the computer methods and storm statistics presented in the preceding sections. The combined total storm tides above NAVD and the associated return periods are plotted on semi-log paper in Figure 10. Each data point represents the average value of five simulations and a curve drawn through the data points is adopted to represent the tide-frequency relationship.




Figure 10: Combined Total Storm Tide Elevation Versus Return Period for Study Area

Table I below gives the combined total storm tide values and corresponding return periods for Martin County.

Table I

Combined Total Storm Tide Levels (ft.) for Various Return Periods

Return Period, TR (years)	North Profile NGVD29	North Profile NAVD88	Middle Profile NGVD29	Middle Profile NAVD88	South Profile NGVD29	South Profile NAVD88
50	9.3	7.9	9.3	7.8	8.7	7.2
30	8.3	6.8	8.2	6.7	7.8	6.3
25	7.8	6.4	7.8	6.3	7.6	6.1
20	7.4	5.9	7.4	5.9	7.2	5.7
15	6.8	5.3	6.8	5.4	6.8	5.2
10	6.0	4.5	6.0	4.5	5.9	4.4
5	4.4	2.9	4.4	2.9	4.3	2.8

*Includes contributions of: wind stress, barometric pressure, dynamic wave set-up and astronomical tide.

REFERENCES

1. Dean, R. G. and Chiu, T. Y., "Combined Total Storm Tide Frequency for Martin County, Florida," Beaches and Shores Resource Center, Florida State University, July 1984.
2. U. S. Department of Commerce, National Oceanic and Atmospheric Administration, "Storm Climatology for the Atlantic and Gulf Coasts of the United States," NOAA Technical Report NWS 38, April 1987.
3. U. S. Department of Commerce, National Oceanic and Atmospheric Administration, National Hurricane Center, "Atlantic hurricane database (HURDAT2) , 1851 – 2012," <http://www.nhc.noaa.gov/data/#hurdat>

APPENDIX A

Summary of Historical Storms affecting Martin County

#	Date	Name	θ_N (degrees)	Y_F (n.mi.)	V_F (knots)	Δp (in.Hg)	R (n.mi.)	Type
1	8/2/1901		114	63	7.3	-0.24		L
2	9/9/1903		108	78	6.5	-1.1	43	L
3	10/12/1904		251	76	9.4	-0.14		E
4	6/14/1906		229	60	15.3	-1.01	26	E
5	10/8/1906		219	50	16.8	-1.77	35	E
6	8/28/1909		90	45	8.9	-0.31		L
7	9/24/1909		233	0	10	-0.14		E
8	10/6/1909		235	93	22.7	-1.66	22	E
9	8/23/1910		178	63	9.0	-0.14		A
10	7/31/1915		138	-104	5.3	-0.68		L
11	8/21/1916		180	-95	11.0	-0.14		E
12	11/11/1916		242	84	32.0	-0.21		E
13	10/15/1921		222	-72	20.0	-0.14		E
14	10/20/1921		248	-124	13.4	-0.74		E
15	10/14/1924		254	64	11.0	-0.80		E
16	11/27/1925		212	-64	16.6	-0.38		E
17	7/22/1926		151	22	9.2	-1.36	14	A
18	10/14/1926		229	87	20.0	-1.89	21	E
19	8/3/1928		138	-12	8.0	-1.07		L
20	9/6/1928		123	30	12.8	-2.48	28	L
21	7/24/1933		90	0	5.3	-0.74		L
22	8/31/1933		122	17	13.8	-1.92	13	L
23	9/23/1935		214	104	9.6	-2.17		E
24	10/30/1935		74	70	11.1	-1.18	10	L
25	6/12/1936		262	76	20.7	-0.33		E
26	8/20/1936		116	-119	20.8	-0.38		L
27	8/7/1939		122	-4	11.3	-0.64		L
28	10/31/1946		138	58	13.4	-0.24		L
29	9/4/1947		76	43	8.2	-1.95	26	L
30	10/9/1947		222	36	10.7	-0.65	13	E
31	9/18/1948		222	9	6.7	-1.45	16	E
32	10/3/1948		233	70	16.6	-1.01	16	E
33	8/23/1949		126	27	12.0	-1.75	23	L
34	9/28/1951	HOW	239	-29	15.5	-0.54		E
35	2/2/1952		218	24	29.0	-0.31		E
36	8/28/1953		241	61	14.2	-0.18		E
37	10/3/1953		207	91	13.5	-0.18		E
38	10/7/1953	HAZEL	234	-50	24.0	-0.56		E
39	6/18/1959		241	-95	32.6	-0.14		E
40	10/17/1959	JUDITH	264	4	28.5	-0.42		E
41	8/26/1962	ALMA	183	-24	15.0	-0.18		E
42	10/8/1964	ISBELL	225	12	20.0	-1.33	13	E
43	9/21/1966	INEZ	72	110	6.5	-0.83		L
44	6/1/1968	ABBY	307	-58	3.3	-0.56		E

#	Date	Name	θ_N (degrees)	Y_F (n.mi.)	V_F (knots)	Δp (in.Hg)	R (n.mi.)	Type
45	9/25/1968		230	50	9.3	-1.48		E
46	10/1/1969	JENNY	202	-89	11.9	-0.14		E
47	9/5/1972	DAWN	233	51	10.0	-0.18		E
48	10/4/1974		172	14	12.1	-0.31		A
49	8/18/1976	DOTTIE	183	4	16.0	-0.21		E
50	6/11/1979		163	38	9.4	-0.14		A
51	8/25/1979	DAVID	149	-1.6	10.5	-1.21	27	A
52	8/7/1981	DENNIS	189	-102	11.1	-0.24		E
53	9/25/1984	ISIDORE	134	46	10.9	-0.39		L
54	10/25/1984		97	0.4	17.0	-0.14		L
55	7/21/1985	BOB	179	-35	11.0	-0.21		E
56	5/24/1987		58	113	9.4	-0.14		L
57	10/9/1987	FLOYD	244	102	15.8	-0.59		E
58	8/21/1988	CHRIS	169	18	14.2	-0.15		A
59	11/17/1988	KEITH	233	-80	16.6	-0.42		E
60	10/15/1991	FABIAN	222	98	17.4	-0.18		E
61	8/16/1992	ANDREW	97	109	20.2	-2.25	10	L
62	11/8/1994	GORDON	234	-42	15.3	-0.53		E
63	7/31/1995	ERIN	122	-40	14.8	-0.92		L
64	8/22/1995	JERRY	138	30	7.5	-0.15		L
65	10/22/1998	MITCH	251	8	28.2	-0.77		E
66	9/19/1999	HARVEY	249	40	27.6	-0.42		E
67	10/12/1999	IRENE	186	-10	8.1	-0.83		E
68	9/11/2001	GABRIELLE	247	-100	7.7	-0.53		E
69	9/3/2003	HENRI	237	-117	14.8	-0.18		E
70	8/25/2004	FRANCES	106	-5	7.4	-1.63	30	L
71	9/2/2004	IVAN	61	63	6.1	-0.12		L
72	9/13/2004	JEANNE	98	-6	10.8	-1.83	26	L
73	8/23/2005	KATRINA	66	60	6.9	-0.74	8	L
74	10/5/2005	TAMMY	156	24	11.0	-0.21		A
75	10/15/2005	WILMA	227	8	26.5	-1.86		E
76	8/24/2006	ERNESTO	192	-80	13.3	-0.39	25	E
77	8/15/2008	FAY	180	-73	4.0	-0.62	33	E
78	9/28/2010	NICOLE	201	113	15.0	-0.56		E


Landfalling Storms = 25; Alongshore Storms = 7; Exiting Storms = 46

¹ Values are estimated prior to landfall.

APPENDIX B

Computed 15 and 25 Year Hydrographs for
Martin County

Martin County
15 -Year Hydrograph



Martin County
25 -Year Hydrograph

